



CLASSIC 2.0 FLEX-2022 3-column

New generation CLASSIC desk frame. Sit & Stand frame with electric motor for an angled desktop. Stable design with continuous height adjustment control for ergonomic working positions.

- Flexible height
- Ergonomic
- Elegant legs of rectangular design

CLASSIC angled electric Sit & Stand frame, with continuous height adjustment control, makes it easy for the user to create an ergonomic work environment. Robust and flexible design that can be adjusted lengthways ensures a reliable desk that is easily adapted to the desktop of your choice. Free-standing legs mean optimum freedom of movement thanks to unrestricted leg room. Elegant legs of rectangular design with the big leg at the bottom. Based on the latest technology in height adjustment control to ensure reliable and comfortable operation.

Art. no	Colour	Stand sections
C31B1213115A17x	Anthracite	3-stage
C31B1213115A14x	Silver	3-stage
C31B1213115A40x	Black	3-stage
C31B1213115A25x	White	3-stage



Technical specifications

CLASSIC 2.0 FLEX-2022 3-column



Specification	Value
Adjustable height	Yes
Powered by	Electricity
Frame width	1740 mm - 2150 mm
Length of side frame	1555 mm - 2145 mm
Stroke	660 mm (615 mm - 1275 mm ± 5 mm)
Lift capacity	Max 150 kg
Speed	40 mm/sec
Standby power	0,1 W
Noise level	< 42 dBa
Dimensions tabletops	1750 - 2650 mm x 700 - 1100 mm 1560 - 2400 mm x 600 - 1100 mm
Certifications	Fulfill Machine directive 2006/42/EC EMC directive 2014/30/EU Low voltage directive 2014/35/EC REACH, WEEE and RoHS 3 2015/863 EN 527-1:2011 Type A, EN 527-2:2016 ISO 21016 UL 962 ETL listed
Duty cycle	10%, 1 min/9 min pause. Max 2 min/18 min
Installation height down position	615 mm
Max bending torque column	Max 200 Nm
Paintwork	Powder coating
Area of use	Indoor environment
Control unit performance	Low inbuilt height dimensions Switching technology without any magnetic fields Inbuilt overload protection Inbuilt temperature protection
Lifetime	Min 10 000 cycles
Ambient temperature	+5° to +30° C
Humidity non condensed	5 - 85% non condensed